

船艇搬运机系列 Series of Marine Hoist

以下每个技术指标都可以根据客户需求调整
Every item below can be customized

www.wowjoint.com

No	Item Equipment Name	WMH-25 25t 船艇搬运机 Marine hoist 25t	WMH-50 50t 船艇搬运机 Marine hoist 50t	WMH-75 75t 船艇搬运机 Marine hoist 75t	WMH-100 100t 船艇搬运机 Marine hoist 100t	WMH-125 125t 船艇搬运机 Marine hoist 125t	WMH-150 150t 船艇搬运机 Marine hoist 150t	WMH-200 200t 船艇搬运机 Marine hoist 200t	WMH-300 300t 船艇搬运机 Marine hoist 300t	WMH-400 400t 船艇搬运机 Marine hoist 400t	WMH-500 500t 船艇搬运机 Marine hoist 500t	WMH-600 600t 船艇搬运机 Marine hoist 600t
1	额定起吊负荷 Rated lifting capacity	25t	50t	75t	100t	125t	150t	200t	300t	400t	500t	600t
2	内净宽 Inside clear width	6.08m	6.64m	7.15m	9.54 m	9 m	11 m	10.9m	11m	11.3m	11.9m	12.4m
3	轴距（轮距） Wheelbase	6.5m	7m	7.5m	9.5m	11m	11m	11 m	12 m	14.65m	18.5m	18.88m
4	跨度 Span	6.8m	8m	8.5m	10.5m	10.655m	12.65m	12.65m	13.5m	13m	14m	15m
5	上横梁下高度(设备内净高) Height under upper cross beam (Inside clear height of machine)	6.43m	8m	8m	8.53m	9.55m	10.5m	10.6m	10.6m	11.74m	12.7m	13.9m
6	最大高度（总高） Overall height	7m	9.3m	9.3m	9.8m	10.77m	13.8m	11.8m	12.3m	13.3m	14.3m	16.5m
7	最大宽度（总宽） Overall width	8m	9.46m	9.96m	12 m	13.24 m	15.6 m	14.4m	15.96m	14.84m	16.24m	17.77m
8	最小转弯半径 Minimum turning radius	9.8m	11m	11.7m	14.53 m	16.5 m	18m	18.2m	20m	24.2m	29.2m	32m
9	自重 Dead weight	25t	40t	50t	60t	75t	83.5t	100 t	150 t	185 t	260 t	320 t
10	吊点（吊带数量） Lifting points (Number of straps)	4（2/4pcs）	4（2/4pcs）	4（2/4pcs）	4（4pcs）	8（4/8pcs）	8（8/16pcs）	8（8/16pcs）	6（6pcs）	8（16pcs）	8（16pcs）	6（12根）
11	起吊速度（空载） Lifting speed (In no-load state)	0-2m/min	0-2m/min	0-2m/min	0-2m/min	0-2m/min	0-2m/min	0-2m/min	0-2m/min	0-2m/min	0-1m/min	0-1m/min
12	起吊速度（满载） Lifting speed (In full load state)	0-1m/min	0-1m/min	0-1m/min	0-1m/min	0-1m/min	0-1m/min	0-1m/min	0-1m/min	0-1m/min	0-0.5m/min	0-0.5m/min
13	行驶速度（空载） Travelling speed (In no-load state)	0-40m/min	0-40m/min	0-40m/min	0-40m/min	0-40m/min	0-40m/min	0-40m/min	0-40m/min	0-40m/min	0-40m/min	0-40m/min
14	行驶速度（满载） Travelling speed (In full load state)	0-20m/min	0-20m/min	0-20m/min	0-20m/min	0-20m/min	0-20m/min	0-20m/min	0-20m/min	0-20m/min	0-20m/min	0-20m/min
15	行驶最大坡度（满载） Maximum slope (full load)	5%	5%	4%	4%	4%	4%	4%	4%	3%	3%	3%
16	转向轮组数量 Number of steering bogies	2	2	2	2	4	4	4	4	8	8	8
17	转向模式 Steering mode	定轴转向 Fixing axle steering	定轴转向 Fixing axle steering	定轴转向 Fixing axle steering	定轴转向 Fixing axle steering	定轴、90 度转向 Fixing axle steering, 90 degree steering	定轴、90 度转向 Fixing axle steering, 90 degree steering	定轴、90 度转向 Fixing axle steering, 90 degree steering	定轴、90 度转向 Fixing axle steering, 90 degree steering	定轴、90 度转向 Fixing axle steering, 90 degree steering	定轴、90 度转向 Fixing axle steering, 90 degree steering	定轴、90 度转向 Fixing axle steering, 90 degree steering
18	操作方式 Operation mode	遥控 Remote control	遥控 Remote control	遥控 Remote control	遥控 Remote control	遥控或驾驶室 Remote control or cabin	遥控或驾驶室 Remote control or cabin	遥控或驾驶室 Remote control or cabin	遥控或驾驶室 Remote control or cabin	遥控或驾驶室 Remote control or cabin	遥控或驾驶室 Remote control or cabin	遥控或驾驶室 Remote control or cabin

其他可选择项 Options

- ◆ 操作方式 Operation mode
- ◆ 驾驶室 Cabin
- ◆ 变吊点 Movable lifting point
- ◆ 可变幅横梁 Variable amplitude cross beam
- ◆ 轮组数 Number of wheel groups
- ◆ 变宽度 Variable width
- ◆ 可变升降行程 Variable lifting stroke
- ◆ 吊点数量 Number of lifting points
- ◆ 变吊重 Variable lifting capacity
- ◆ 客户定制 Customized